

SKID STEER LOADER

ZJ30-ZJ120



Specifications

	ZJ30	ZJ40	ZJ45	ZJ60	ZJ65	ZJ100	ZJ120
Operating load (kg)	300	500	700	850	1050	1100	1200
Max Speed (km/h)	9	10	12	12	12	9\18	9\18
Rated flux (L/min)	50	60	62.5	75	75	75	75
High Flow Flux (L/min)	/	/	/	/	120	140	140
Tire (track) model	23x8.5-15	8.5-15	10-16.5	12-16.5	12-16.5	12-16.5	12-16.5
Rated power (Kw)	18.4	37	37	45	55	74	103
Fuel tank capacity (L)	25	60	70	80	75	90	90
self weight bucket (kg)	1500	2300	2700	2800	3500	3550	3600
Bucket capacity (m³)	0.2	0.3	0.4	0.4	0.5	0.55	0.55

Dimension Parameter

	ZJ30	ZJ40	ZJ45	ZJ60	ZJ65	ZJ100	ZJ120
A. Overall operating height (mm)	3590	3300	3980	4000	4070	4070	4070
B. Height to bucket hinge pin (mm)	2650	2725	3080	3100	3280	3280	3280
C. Hheight to top of cab (mm)	2050	2000	2140	2160	2160	2160	2160
D. Height to bottom of level bucket(mm)	2470	2558	2913	2933	3140	3140	3140
E. Without bucket length (mm)	2430	2300	2640	2750	2880	2880	2880
F. Overall length with bucket(mm)	3170	2950	3420	3490	3580	3580	3580
G. Dumping angle at maximum height(°)	40	40	40	40	40	40	40
H. Dumping height(mm)	1920	2050	2380	2400	2500	2500	2500
I. Dumping reach(mm)	720	790	700	750	700	700	700
J. Rollback of bucket on ground(°)	30	30	30	30	30	30	30
K. Rollback of bucket at full height(°)	104	104	104	104	104	104	104
L. Wheelbase(mm)	801	897	991	991	1080	1115	1115
M. Ground clearance(mm)	180	140	185	205	205	205	205
N. Angle of departure(°)	20	20	20	20	20	20	20
O. Front turning radius without bucket(mm)	971	1098	1168	1198	1250	1278	1278
P. Front turning radius(mm)	1681	1760	1958	1958	2112	2144	2144
Q. Rear turning radius(mm)	1371	1296	1630	1728	1774	1857	1857
R. Rear axle to bumper (mm)	940	964	1108	1208	1082	1082	1082
S. Thread width (mm)	882	1080	1450	1500	1500	1500	1500
T. Width (mm)	1110	1350	1720	1880	1880	1880	1880
U. Bucket width (mm)	1150	1400	1740	1880	1880	1880	1880

